



-----Disclaimer-----

Luminaire performance data is provided by manufacturer(s) and is based on IESNA testing procedures done in controlled laboratory conditions. Field results may vary from computer modeling due to numerous factors (beyond our control). This photometric modeling is based upon information and criteria provided to us and is solely for design assistance; final lighting design, application, fixture selection and layout is the responsibility of the specifier of record.

Calculation Summary							
Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min
EAST-20' SPILL LIGHT	Illuminance	Fc	0.29	2.4	0.0	N.A.	N.A.
NORTH-20' SPILL LIGHT	Illuminance	Fc	0.00	0.1	0.0	N.A.	N.A.
SOUTH-20' SPILL LIGHT_1	Illuminance	Fc	0.11	0.5	0.0	N.A.	N.A.
VEHICULAR HARDSCAPE_Planar	Illuminance	Fc	2.54	4.5	1.0	2.54	4.50
WEST-20' SPILL LIGHT	Illuminance	Fc	0.02	0.1	0.0	N.A.	N.A.

Luminaire Schedule							
Symbol	Qty	Label	Arrangement	Luminaire Lumens	Luminaire Watts	LLF	Description
	3	B4_BB	Back-Back	3434	54	0.850	SELUX // ACL-X-R4-5G1800-30-XX-UNV-HS
	14	B4	Single	3434	54	0.850	SELUX // ACL-X-R4-5G1800-30-XX-UNV-HS

